

2 Cranberry Road, Unit A4, Parsippany, NJ 07054,USA Tel: 862-210-8344 Fax: 862-210-8336 Sales@applechem.com

Technical Data Sheet of Ggel CCT 200

Product Description

A gel mixture of organo-modified clay in cosmetic oils for rheology control

Legislation

 INCI Caprylic/Capric Triglyceride(and) Stearalkonium Bentonite (and) Propylene Carbonate

CAS # (65381-09-1;73398-61-5)/130501-87-0/108-32-7
 EINECS/ELINCS (265-724-3; 277-452-2)//436-020-5/203-572-1

General Product Specification

<u>ltem</u>	<u>Specification</u>
Appearance	A stable green/gray paste gel
Viscosity	3 – 10 million cP, Brookfield viscometer, Spindle TG, 1 rpm

Toxicity profile

- All components are commonly acceptable cosmetic ingredients which are not known to be hazardous to the health
- No animal and no-GMO derived ingredients

Features/Benefits

- Very stable gel, no separation overtime
- Predictable, reproducible and stable shear-thinning viscosity control

------ Create Possibilities -----Last product specification update: 7/1/2010 Last document update: 4/24/2017

- Excellent suspension of pigments, actives, additives, etc. in the oil phase
- Stabilize W/O emulsion
- Provide a smooth and lubricating sensory to skin
- Can be easily incorporated into the formulation during manufacturing

Applications

Cosmetic and Toiletry:

- Foundations and other color cosmetics
- Skin care lotions and creams
- Antiperspirants

How to use it?

- Add the Ggel CCT 200, under medium or high shear, to a portion of the organic components with
 which it is mutually compatible. Mix until homogenous before adding other ingredients. Take into
 account the potential large difference between the Ggel and the lower viscosity component into
 which it is mixing, when choose the right mixing equipment. Typical cosmetic equipments such
 as homogenizer would work.
- When using only low-shear mixing equipment, stir the Ggel alone and then slowly add the most compatible component by portions, always ensuring the mixture remains homogeneous at each stage.
- Normal dosage is 3 15% of the oil phase.

Packaging

Product is available in 18 kg /5 gallon pail and 180 kg / 55 gallon drum

Storage

 Store the product in its original package, sealed tightly, and protect it from exposure to high temperatures

Due to variations in methods, conditions, and equipment used commercially in processing these materials, no warranties or guarantees are made as to the suitability of information or products for the application disclosed. Nothing contained herein is to be considered as permission, recommendation, nor as inducement to practice any patented invention without the permission of the patent owner. Applechem shall not be liable and the User assumes all risk and responsibility for any use or handling of any material beyond Applechem's direct control.